

EBC-AT serie

	EBC 12-20AT	EBC 12-30AT	EBC 12-50AT	EBC 24-15AT
Ingangsspanning <i>Input Voltage</i>	170 – 270Vac, 50/60Hz			
Uitgangsspanning nominaal <i>Output voltage (nominal)</i>	12Vdc			24Vdc
Laadspanningen <i>Charge voltages</i>	Start/semi VLRA Calcium	14,6 Vdc / 13,5 Vdc 14,2 Vdc / 13,8 Vdc 14,8 Vdc / 13,8 Vdc		29,2 Vdc / 27,0 Vdc 28,4 Vdc / 27,6 Vdc 29,6 Vdc / 27,6 Vdc
Laad karakteristiek <i>Charge curve</i>	IUoUoe			
Laadstroom max. <i>Maximum charge current</i>	20 Amp.	30 Amp.	50 Amp.	15 Amp.
Max. lichtnetbelasting bij 230Vac <i>Max. lighting load at 230Vac</i>	2,35 Amp.	3,35 Amp.	5,60 Amp.	3,10 Amp.
Aantal uitgangen <i>Battery banks</i>	2			
Rendement <i>Efficiency</i>	Max. 88%			
Max. luchtvochtigheid <i>Max. relative humidity</i>	80%			
Koeling <i>Ventilation</i>	Electronisch gestuurde ventilator <i>Electronically controlled fan</i>			
Batterij aansluiting <i>Battery connection</i>	Schroefuitgang <i>Terminal blocks</i>			
Galvanisch gescheiden <i>Galvanic separated</i>	Ja Yes			
Behuizing <i>Housing</i>	Aluminium <i>Aluminium</i>			
Beschermingsgraad (EMC) <i>Level of protection (EMC)</i>	IP 205			
Afmetingen (lxbxh in mm) <i>Dimentions (lwxhx mm)</i>	200x215x80	240x235x80	280x235x80	240x235x80
Gewicht (kg) <i>Weight (kg)</i>	1,9	2,5	3	2,5
