

IPC / PB series

	PB 1108	IPC 1205
Ingangsspanning <i>Input voltage</i>	8-16 VDC	10-16 VDC
Uitgangsspanning <i>Output voltage</i>	13,8 VDC	27,6 VDC
Continu vermogen <i>Cont. power</i>	8 Amp.	5 Amp.
Max. vermogen <i>Max. load</i>	9 Amp.	5,5 Amp.
Galvanisch gescheiden <i>Galvanic isolated</i>	Ja Yes	
Rendement <i>Efficiency</i>	90%	
Rimpel <i>Ripple</i>	50mV RMS	
Beveiligingen <i>Protections</i>	Onderspanning, overbelasting, kortingsluiting (uitgang), temperatuur <i>Under voltage, overload, short circuit (output), temperature</i>	
Parallel schakelbaar <i>Parallel operation</i>	Ja Yes	
Omgevingstemperatuur <i>Operation temperature</i>	-20°C - 50°C	
Verbruik onbelast aan/uit <i>Current draw at no load on/off</i>	140mA / 8mA	325mA / 15mA
Aansluiting ingang <i>Input connection</i>	Vaste kabel <i>Fixed cable</i>	
Aansluiting uitgang <i>Output connection</i>	Schroefuitgang <i>Terminal blocks</i>	
Koeling <i>Cooling</i>	Ventilator <i>Fan</i>	
Afmetingen lxbxh cm <i>Demensions</i>	10 x11,5x7	10x11,5x7
Gewicht kg <i>Weight kg</i>	0,75	0,75

